

BE A LEADER IN
PRODUCTIVITY

LIDER TTD

COMPARE!



POWER

DURABILITY

QUALITY

JM5050 TTD

JM2050 TTD



FERTILIZER
DISTRIBUTORS

Jumil



The difference is here!




Centralized cardam
Better move handling.



Track width
Track with full double lane. Strength for wet organic products. More homogeneous distribution.



Deflectors (optional)
To targeted chemical or organic fertilizers applications.



Microdoser
Has 1:1 gear transmission to work with a double pulley or 1:2 with simple pulley. Maintains distribution speed.

Model	JM LD2050 TTD Gauge 1,60m	JM LD2050 TTD Gauge 1,30m	JM LD5050TTD	JM LD5050 TTD Pantaneira
Load Volume	1,6m³		3,4m³	
Maximum load capacity	3000kg		6000kg	
Track width	800mm			
Minimum power required	50cv		65cv	
Tires	7.50x10 – 10 canvas		14.9-24 10 canvas*	
Tire Amount	2		4	2
Wheel set system	Simple		Simple tandem	Swamp
Gauge	1,50m	1,30m	1,60m	2,00m
Recommended working speed	Until 08km/h			
Width	1540			
Length	4000		4500	
Height	1500		1700	
Weight	1280	1257	1584	1520



Jumil - Justino de Moraes, Irmãos Sv/A
Rua Ana Luiza, 568 - CEP: 14.300-000 - Batatais/SP
Tel.: 16 3660-1000 - Fax 16 - 3660-1110
Email: vendasmaq@jumil.com.br
www.jumil.com.br

Distribuidor autorizado